

PROFESSIONAL LINE

FISSATIVO ACRILICO PIGMENTATO

Exterior high impregnation consolidating primer

CODE 13-193


DESCRIPTION AND USE

Pigmented acrylic fixative deeply absorbing into the surface. It is highly recommended as base coat for interior and exterior walls. It improves plasters absorption and in the meantime consolidates the base coat to paint.

The pigmentation gives an initial covering helping the application and improving the final result.

Aspect of the dry film: covering matt

APPLICATION DATA

1 h DRY FOR TOUCH	12 h RECOAT TIME	5 m²/l SPREAD RATE Civil plaster	 30% v/v	
--------------------------------	-------------------------------	---	--	--

TECHNICAL DATA

COMPOSITION	Special acrylic polymers in water dispersion, titanium dioxide and calibrated extenders
SPECIFIC GRAVITY	1.550±0.030 g/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	46%
V.O.C.	< 30 g/L
AVERAGE VISCOSITY	(Brookfield rot. No.5 at 2rpm at 21°C): 100 Poises
PACKAGING	14000 ml
STORAGE	Keep from freezing. Store in a cool and dry place

Revision No. 0 dated February 2009

PAINT SYSTEM

- **New walls:** thoroughly clean with a coat of Fissativo Acrilico Pigmentato; wait at least 12 hours then apply finishing products such as Farina Acrilico, Quarzo, Scudo.

N.B.: Do not apply Silicate or Lime paints over this product.

- **Walls to repaint:** remove all loose paint and if necessary smooth the surface with specific products (especially in case of exterior walls). Apply one coat of Fissativo Acrilico Pigmentato diluted as per given instructions and finish as New walls.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.
If products are not used beyond our control our liability is limited to the quality of the product itself.