

DECORATIVE LINE

LUCE

Monochrome decorative finish, interactive effect

CODE

Gold: 18-600 – Silver: 18-601

DESCRIPTION AND USE

Monochromatic decorative acrylic-based finish with interactive effect due to features of optical physics such as interference and reflexion. According to the angle of view it gives different interplays of colours.

Easy to apply, nice to the touch and easy to wash (after at least 15 days from the last application). It is suitable to decorate either private residence or public spaces where you wish to realize a unique decoration, particularly reflectant when hit by direct spotlight or skim light. The effect is obtained by using two products: Luce Fondo and Luce Finitura. Luce Finitura is available in both GOLD and SILVER.

LUCE FONDO APPLICATION DATA

½ h DRY TO TOUCH	min 6h RECOAT TIME	5 m²/l SPREAD RATE Two coats	 WOOL ROLL max 5%v/v	
----------------------------	------------------------------	---	---	---

LUCE FONDO TECHNICAL DATA

COMPOSITION	Based on modified acrylic copolymers, pigments, fillers and selected additives
SPECIFIC GRAVITY	1.350 ± 0.020 g/L
FALSH POINT	Not flammable
SOLIDS BY VOLUME	34%
AVERAGE VISCOSITY	15000 cps (Brookfield rot. No. 3 / 2 rpm at 21°C)
COLOURS	See color card
TINTING	Toner (250 cc): 2 in 4 lts. - 6 in 12 lts. Tingo: see formulary
PACKAGING	4000 ml - 12000 lml

Revision No. 1 dated 14/01/2008

WARNINGS

- Keep from freezing
- Shake well before use
- Clean the tools with water after use
- Store in a dry place away from sunlight

LUCE FINITURA APPLICATION DATA

½ h DRY TO TOUCH	15 m²/l SPREAD RATE One coat	 WOOL ROLLER MAX 5%V/V	
----------------------------	---	---	---

LUCE FINITURA TECHNICAL DATA

COMPOSITION	based on acrylic copolymers, Gold & Silver pearly pigments, extenders, body agents and selected additives
SPECIFIC GRAVITY	1.050 ± 0.020 g/L
FALSH POINT	Not flammable
SOLIDS BY VOLUME	25%
AVERAGE VISCOSITY	10000 cps (Brookfield rot. No. 3 / 2 rpm at 21°C)
COLOURS	See color card
TINTING	Glitter Gold or Silver (250ml) 1X4 L - 75ml X1 L Color Card Toner (250 ml): 1x4 L - ¼ x 1 L Tingo: see formulary
PACKAGING	1000 ml – 4000 ml

WARNINGS

- Keep from freezing
- Shake well before use
- Clean the tools with water after use
- Store in a dry place away from sunlight

PAINT SYSTEM

New walls:

Apply one brush coat of Fissativo Acrilico (diluted 1:7 with water). Wait at least 4 hours and apply two coats of Luce Fondo with a wool roller, waiting 6 hours between the two coats. After 24 hours, apply one coat of Luce Finitura with a wool roller.

N.B.: Luce Finitura must be applied in large quantities (see spread rate), criss-crossing and finishing with vertical movement in order to achieve an excellent final result.

Walls already painted:

- With washable water-based paint: fill holes and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Fissativo Acrilico (diluted 1:7 with water) only over patched areas. Wait at least 4 hours and apply two coats of Luce fondo with a wool roller, waiting 6 hours between the two coats. After 24 hours, apply one coat of Luce Finitura with a wool roller.
- With distemper, lime paint or chalky paint: fill holes and imperfections with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Fissativo Acrilico (diluted 1:6 with water) over the whole surface. Wait at least 4 hours and apply two coats of Luce Fondo with wool roller, waiting 6 hours between the two coats. After 24 hours, apply one coat of Luce Finitura with wool roller.

N.B.: Luce Finitura must be applied in large quantities (see spread rate), criss-crossing and finishing with vertical movement in order to achieve an excellent final result.

Orazio Brignola S.p.A. reserves the right to update the above data which are given for information only.
If products are not used beyond our control our liability is limited to the quality of the product itself.